

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 09.12.2017

Page 1 of 26

Revision date: 04.10.2019

Butyl Liner Sealer

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product Name: Butyl Liner Sealer

Product code: 739

Additional information: Rev 6

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Liner sealer

Uses advised against: Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

1.3 Details of the manufacturer/supplier of the safety data sheet

Manufacturer:

North America

Tech International
200 East Coshocton Street
Johnstown, OH 43031
1-740-967-9015
www.tech-international.com

Supplier:

European Union

Tech International Europe
Koeyleuken 16
2300 Turnhout, Belgium
00 32 1442 3103
info@techeurope.co.uk

1.4 Emergency telephone number:

Belgium

CHEMTREC

Brussels +(32) - 28083237

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture:

Classification according to Regulation (EC) No. 1272/2008 (CLP):

Flammable liquids, category 2

Skin irritation, category 2

Skin sensitization, category 1

Specific target organ toxicity - single exposure, category 3, central nervous system

Reproductive toxicity, category 2

Chronic aquatic hazard, category 2

Hazard-determining components of labeling:

2,2'-Methylenebis(4-methyl-6-tertiarybutyl phenol)

Zinc oxide

Di(benzothiazol-2-yl) disulphide

Thiram (ISO); tetramethylthiuram disulphide

Heptane, branched, cyclic and linear

Heptane

2.2 Label elements

Hazard pictograms:



Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 09.12.2017

Page 2 of 26

Revision date: 04.10.2019

Butyl Liner Sealer

Signal word: Danger

Hazard statements:

- H225 Highly flammable liquid and vapor.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H336 May cause drowsiness or dizziness.
- H361 Suspected of damaging fertility or the unborn child.
- H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233 Keep container tightly closed.
- P240 Ground and bond container and receiving equipment.
- P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
- P242 Use non-sparking tools.
- P243 Take action to prevent static discharges.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P264 Wash skin thoroughly after handling.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P271 Use only outdoors or in a well-ventilated area.
- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P273 Avoid release to the environment.
- P302+P352 IF ON SKIN: Wash with plenty of water/soap.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P333+P313 If skin irritation or a rash occurs: Get medical advice/attention
- P308+P313 If exposed or concerned: Get medical advice/attention
- P312 Call a POISON CENTER/doctor/physician if you feel unwell.
- P321 Specific treatment (see supplemental first aid instructions on this label).
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P370+P378 In case of fire: Use agents recommended in Section 5 to extinguish.
- P391 Collect spillage
- P405 Store locked up.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards: None known

SECTION 3: Composition/information on ingredients

3.1 Substance: Not applicable.

3.2 Mixture:

Identification	Name	Classification according to Regulation (EC) No. 1272/2008 (CLP)	Weight %
CAS number: 426260-76-6	Heptane, branched, cyclic and linear	Asp. Tox. 1; H304 Aquatic Chronic 2; H411 Flam. Liq. 2; H225 Stot SE 3; H336 Skin Irrit. 2 ; H315	70-80

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 09.12.2017

Page 3 of 26

Revision date: 04.10.2019

Butyl Liner Sealer

CAS number: 1333-86-4 EC number: 215-609-9	Bounded Carbon Black	Not classified	5-10
CAS number: 142-82-5 EC number: 205-563-8	Heptane	Asp. Tox. 1; H304 Skin Irrit. 2 ; H315 Stot SE 3; H336 Flam. Liq. 2; H225 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	<3
CAS number: 64742-54-7 EC number: 265-157-1	Distillates (petroleum), hydrotreated heavy paraffinic	Not classified	1-1.5
CAS number: 9002-88-4	Polyethylene	Not classified	0.25-0.75
CAS number: 120-78-5 EC number: 204-424-9	Di(benzothiazol-2-yl) disulphide	Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	<0.5
CAS number: 57-11-4 EC number: 200-313-4	Stearic acid	Not classified	<0.5
CAS number: 1314-13-2 EC number: 215-222-5	Zinc oxide	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	<0.5
CAS number: 137-26-8 EC number: 205-286-2	Thiram (ISO); tetramethylthiuram disulphide	Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Sens. 1; H317 Skin Irrit. 2 ; H315 Eye Irrit. 2; H319 Stot RE 2; H373 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	<0.25
CAS number: 119-47-1 EC number: 204-327-1	2,2'-Methylenebis(4-methyl-6- tertiarybutyl phenol)	Repr. 2; H361 Aquatic Chronic 4; H413	<0.2
CAS number: 1309-48-4 EC number: 215-171-9	Magnesium oxide	Not classified	<0.15
CAS number: 8042-47-5 EC number: 232-455-8	White Mineral Oil	Not classified	<0.01

Additional information:

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 09.12.2017

Page 4 of 26

Revision date: 04.10.2019

Butyl Liner Sealer

Carbon black is classified as a carcinogen only in its respirable form. Since the carbon black in this product is not respirable, the product itself is not classified as a carcinogen in the form presented.

According to Note L of the European Directive 67/548/CEE, the "solvent neutral oil" substance should not be classified as "carcinogenic" ingredients, because it has been shown that the substances contain less than 3% DMSO extract as measured by IP 346.

Full Text of H and EUH statements: See section 16

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes:

Not determined or not available.

Following inhalation:

Loosen clothing as necessary and position individual in a comfortable position

Maintain an unobstructed airway

Get medical advice/attention if you feel unwell

Following skin contact:

Rinse affected area with soap and water

If symptoms develop or persist, seek medical attention

Take off all contaminated clothing

Gently blot or brush away excess product

Wash with plenty of lukewarm, gently flowing water

Get medical advice if skin irritation occurs or you feel unwell

Following eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes

If symptoms develop or persist, seek medical attention

Following ingestion:

Rinse mouth thoroughly

Seek medical attention if irritation, discomfort, or vomiting persists

4.2 Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

Not determined or not available.

Delayed symptoms and effects:

Not determined or not available.

4.3 Indication of any immediate medical attention and special treatment needed

Specific treatment:

Not determined or not available.

Notes for the doctor:

Not determined or not available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:

Use Water (fog only), dry chemical, chemical foam, carbon dioxide, or alcohol-resistant foam.

Unsuitable extinguishing media:

Not determined or not applicable.

5.2 Special hazards arising from the substance or mixture:

Thermal decomposition can lead to release of irritating gases and vapors.

Vapors can flow to distant ignition sources and flashback.

Liquid is volatile and may generate an explosive atmosphere.

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 09.12.2017

Page 5 of 26

Revision date: 04.10.2019

Butyl Liner Sealer

May form corrosive mixtures with water.

5.3 Advice for firefighters

Personal protection equipment:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit.

Special precautions:

Shut off sources of ignition.

Carbon monoxide and carbon dioxide may form upon combustion.

Heating causes a rise in pressure, risk of bursting and combustion.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation.

Ensure air handling systems are operational.

Wear protective eye wear, gloves and clothing.

Beware of vapors accumulating to form explosive concentrations.

Vapors can accumulate in low areas.

6.2 Environmental precautions:

Should not be released into the environment.

Prevent from reaching drains, sewer or waterway.

6.3 Methods and material for containment and cleaning up:

Wear protective eye wear, gloves and clothing.

Use spark-proof tools and explosion-proof equipment.

Absorb with non-combustible liquid-binding material (sand, diatomaceous earth (clay), acid binders, universal binders).

Dispose of contents / container in accordance with local regulations.

6.4 Reference to other sections:

Not determined or not applicable.

SECTION 7: Handling and storage

7.1 Precautions for safe handling:

Use only with adequate ventilation.

Avoid breathing mist or vapor.

Do not eat, drink, smoke or use personal products when handling chemical substances.

Take precautionary measures against electrostatic discharges.

Use only non-sparking tools.

7.2 Conditions for safe storage, including any incompatibilities:

Keep container tightly sealed.

Protect from freezing and physical damage.

Store in a cool, well-ventilated area.

Store away from all ignition sources (open flames, hot surfaces, direct sunlight, spark sources).

7.3 Specific end use(s):

Not determined or not applicable.

SECTION 8: Exposure controls/personal protection

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 09.12.2017

Page 6 of 26

Revision date: 04.10.2019

Butyl Liner Sealer



8.1 Control parameters

Only those substances with limit values have been included below.

Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
Hungary	White Mineral Oil	8042-47-5	Ceiling Limit (MK Value): 5 mg/m ³ [Oil smog (mineral oil)]
	Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	Ceiling Limit (MK Value): 5 mg/m ³ (Oil smog, mineral oil)
	Heptane	142-82-5	8-hour TWA (ÁK Value): 2000 mg/m ³
	Polyethylene	9002-88-4	8-hour TWA: 10 mg/m ³ (Other inert dusts, total (inhalable))
	Heptane	142-82-5	60-minute STEL (CK value): 8000 mg/m ³
	Polyethylene	9002-88-4	8-hour TWA: 6 mg/m ³ (Other inert dusts, respirable)
	Magnesium oxide	1309-48-4	8-hour TWA (ÁK Value): 6 mg/m ³ (respirable, as Mg)
	Magnesium oxide	1309-48-4	60-minute STEL (CK Value): 24 mg/m ³ (respirable, as Mg)
	Magnesium oxide	1309-48-4	8-hour TWA (ÁK Value): 10 mg/m ³ (total, inhalable)
	Zinc oxide	1314-13-2	8-hour TWA (ÁK Value): 5 mg/m ³ (Respirable)
	Magnesium oxide	1309-48-4	8-hour TWA (ÁK Value): 6 mg/m ³ (respirable)
	Zinc oxide	1314-13-2	60-minute STEL (CK Value): 20 mg/m ³ (Respirable)
Czech Republic	Heptane, branched, cyclic and linear	426260-76-6	8-hour TWA: 1000 mg/m ³
	Heptane, branched, cyclic and linear	426260-76-6	Ceiling limit: 2000 mg/m ³
	Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	The ceiling limit (NPK-P): 10 mg/m ³ (Mineral oils, aerosol)
	Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	8-hour TWA: 5 mg/m ³ (Mineral oils, aerosol)
	Polyethylene	9002-88-4	8-hour TWA: 5.0 mg/m ³
	Bounded Carbon Black	1333-86-4	Government Decree 361/2007 Sb.: TWA 2.0 mg/m ³ (8 hr)
	White Mineral Oil	8042-47-5	8-hour TWA: 5 mg/m ³ (aerosol)
	Heptane	142-82-5	8-hour TWA: 1000 mg/m ³
	Heptane	142-82-5	Ceiling limit (NPK-P): 2000 mg/m ³
	White Mineral Oil	8042-47-5	Ceiling limit (NPK-P): 10 mg/m ³ (aerosol)
	Zinc oxide	1314-13-2	8-hour TWA: 2 mg/m ³ (as Zn)

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 09.12.2017

Page 7 of 26

Revision date: 04.10.2019

Butyl Liner Sealer

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Zinc oxide	1314-13-2	Ceiling limit (NPK-P): 5 mg/m ³ (Fumes)
Lithuania	Stearic acid	57-11-4	8-hour TWA: 5 mg/m ³
	White Mineral Oil	8042-47-5	8-hour TWA: 1 mg/m ³ (Oil mist, including smoke)
	White Mineral Oil	8042-47-5	15-minute STEL: 3 mg/m ³ (Oil mist, including smoke)
	Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	8-hour TWA: 1 mg/m ³ (Oil mist, including smoke)
	Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	15-minute STEL: 3 mg/m ³ (Oil mist, including smoke)
	Thiram (ISO); tetramethylthiuram disulphide	137-26-8	8-hour TWA: 1 mg/m ³
	Thiram (ISO); tetramethylthiuram disulphide	137-26-8	15-minute STEL: 2 mg/m ³
	Heptane	142-82-5	8-hour TWA: 2085 mg/m ³ (500 ppm)
	Heptane	142-82-5	15-minute STEL: 3128 mg/m ³ (750 ppm)
	Magnesium oxide	1309-48-4	8-hour TWA: 4 mg/m ³
	Magnesium oxide	1309-48-4	8-hour TWA: 10 mg/m ³ (inhalable fraction)
	Magnesium oxide	1309-48-4	8-hour TWA: 5 mg/m ³ (respirable fraction)
	Zinc oxide	1314-13-2	8-hour TWA: 5 mg/m ³
	Magnesium oxide	1309-48-4	8-hour TWA: 1 mg/m ³ (textile dust)
	Polyethylene	9002-88-4	8-hour TWA: 10 mg/m ³
	Polyethylene	9002-88-4	8-hour TWA: 10 mg/m ³ (dust, inhalable fraction)
	Polyethylene	9002-88-4	8-hour TWA: 5 mg/m ³ (Dust: respirable fraction)
Polyethylene	9002-88-4	8-hour TWA: 1 mg/m ³ (Dust - textile)	
Polyethylene	9002-88-4	8-hour TWA: 5 mg/m ³ (Dusts and mists of organic origin, inhalable fraction)	
Belgium	Stearic acid	57-11-4	8-hour TWA: 10 mg/m ³ (as stearates)
	Bounded Carbon Black	1333-86-4	Exposure Limit Value: TWA 3.5 mg/m ³ (8 hr)
	White Mineral Oil	8042-47-5	8-hour TWA: 5 mg/m ³ [Mineral oils (mist)]
	White Mineral Oil	8042-47-5	15-minute STEL: 10 mg/m ³ [Mineral oils (mist)]
	Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	8-Hour TWA: 5 mg/m ³ (Mineral oils, mist)
	Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	15-minute STEL: 10 mg/m ³ (Mineral oils, mist)
	Thiram (ISO); tetramethylthiuram disulphide	137-26-8	8-hour TWA: 0.005 ppm (0.05 mg/m ³)

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 09.12.2017

Page 8 of 26

Revision date: 04.10.2019

Butyl Liner Sealer

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Heptane	142-82-5	8-hour TWA: 400 ppm (1664 mg/m ³)
	Heptane	142-82-5	15-minute STEL: 500 ppm (2085 mg/m ³)
	Magnesium oxide	1309-48-4	8-hour TWA: 10 mg/m ³ (fumes)
	Zinc oxide	1314-13-2	8-hour TWA: 5 mg/m ³ (Fumes)
	Zinc oxide	1314-13-2	15-minute STEL: 10 mg/m ³ (Fumes)
	Zinc oxide	1314-13-2	8-hour TWA: 10 mg/m ³ (Dusts)
	Polyethylene	9002-88-4	8-hour TWA: 10 mg/m ³ (Particles not otherwise classified. Inhalable fraction)
	Polyethylene	9002-88-4	8-hour TWA: 3 mg/m ³ (Particles not otherwise classified. Respirable fraction)
Bulgaria	Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	TWA: 5.0 mg/m ³ (Oil - Mineral, petroleum)
	Polyethylene	9002-88-4	TWA: 10 mg/m ³ (Dust)
	Polyethylene	9002-88-4	TWA: 5.0 mg/m ³ (Mixed dusts, containing less than 2% free crystalline silicon dioxide, inhalable fraction)
	Polyethylene	9002-88-4	TWA: 3.5 mg/m ³ (Mixed dusts, containing less than 2% free crystalline silicon dioxide, respirable fraction)
	Thiram (ISO); tetramethylthiuram disulphide	137-26-8	TWA: 4.0 mg/m ³
	Polyethylene	9002-88-4	TWA: 10 mg/m ³ (Insoluble dusts, containing less than 2% free crystalline silicon dioxide (not containing fibrous particles), not listed elsewhere, inhalable fraction)
	Polyethylene	9002-88-4	TWA: 4 mg/m ³ (Insoluble dusts, containing less than 2% free crystalline silicon dioxide (not containing fibrous particles), not listed elsewhere, respirable fraction)
	White Mineral Oil	8042-47-5	TWA: 5.0 mg/m ³ (petroleum)
	Polyethylene	9002-88-4	TWA: 5 mg/m ³ (Refinery and smelter coke powder, inhalable fraction)
	Magnesium oxide	1309-48-4	TWA: 10.0 mg/m ³
	Heptane	142-82-5	TWA: 1600 mg/m ³
Zinc oxide	1314-13-2	15-minute STEL: 10.0 mg/m ³	
Ireland	Stearic acid	57-11-4	8-hour TWA: 10 mg/m ³ (as stearates, except lead stearate)
	Bounded Carbon Black	1333-86-4	2016 Code of Practice for Chemical Agents Regulations 2001: TWA 3.0 mg/m ³ (8 hr) OEL

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 09.12.2017

Page 9 of 26

Revision date: 04.10.2019

Butyl Liner Sealer

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	8-hour OEL (TWA) is: 5 mg/m ³ (Mineral oil, pure, highly and severely refined; Inhalable fraction)
	White Mineral Oil	8042-47-5	8-hour OEL (TWA): 5 mg/m ³ (Mineral oil, pure, highly and severely refined; Inhalable fraction)
	Thiram (ISO); tetramethylthiuram disulphide	137-26-8	8-hour OEL (TWA): 0.05 mg/m ³
	Heptane	142-82-5	8-hour OEL (TWA): 500 ppm (2085 mg/m ³)
	Magnesium oxide	1309-48-4	8-hour OEL (TWA): 4 mg/m ³ (respirable dust)
	Magnesium oxide	1309-48-4	8-hour OEL (TWA): 5 mg/m ³ (fume)
	Magnesium oxide	1309-48-4	15-minute OEL (STEL): 10 mg/m ³ (fume)
	Magnesium oxide	1309-48-4	8-hour OEL (TWA): 10 mg/m ³ (total inhalable dust)
	Polyethylene	9002-88-4	8-hour (OEL) TWA: 10 mg/m ³ (Dust: non-specific, total inhalable)
	Polyethylene	9002-88-4	8-hour (OEL) TWA: 4 mg/m ³ (Dust: non-specific, respirable)
Poland	White Mineral Oil	8042-47-5	8-hour TWA (NDS): 5 mg/m ³ (Highly refined mineral oils with the exception of cutting fluids, Inhalable fraction)
	Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	8-hour TWA (NDS): 5 mg/m ³ (Highly refined mineral oils with the exception of cutting fluids, inhalable fraction)
	Bounded Carbon Black	1333-86-4	Dz.U.Poz. 817/2014, Annex 1: TWA (NDS) 4.0 mg/m ³ (8 hr)
	Thiram (ISO); tetramethylthiuram disulphide	137-26-8	8-hour TWA (NDS): 0.5 mg/m ³
	Heptane	142-82-5	8-hour TWA (NDS): 1200 mg/m ³
	Heptane	142-82-5	15-minute STEL (NDSCh): 2000 mg/m ³
	Zinc oxide	1314-13-2	8-hour TWA (NDS): 5 mg/m ³ (Inhalable fraction, as Zn)
	Zinc oxide	1314-13-2	15-minute STEL (NDSCh): 10 mg/m ³ (Inhalable fraction, as Zn)
	Magnesium oxide	1309-48-4	8-hour TWA (NDS): 10 mg/m ³ (inhalable fraction)
Polyethylene	9002-88-4	8-hour TWA: 10 mg/m ³ (Other nontoxic industrial dusts, including those containing less than 2% free (crystalline) silica, inhalable fraction)	

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 09.12.2017

Page 10 of 26

Revision date: 04.10.2019

Butyl Liner Sealer

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Polyethylene	9002-88-4	8-hour TWA: 6 mg/m ³ (Dusts of apatites and phosphate rocks containing less than 2% free crystalline silica, inhalable fraction)
	Polyethylene	9002-88-4	8-hour TWA: 2 mg/m ³ (Dusts of apatites and phosphate rocks containing less than 2% free crystalline silica, respirable fraction)
	Polyethylene	9002-88-4	8-hour TWA: 4 mg/m ³ (Dusts of apatites and phosphate rocks containing more than 2% free crystalline silica, inhalable fraction)
	Polyethylene	9002-88-4	8-hour TWA: 1 mg/m ³ (Dusts of apatites and phosphate rocks containing more than 2% free crystalline silica, respirable fraction)
Italy	Stearic acid	57-11-4	8-hour TWA: 3 mg/m ³ [Stearates (except stearates of toxic metals), Respirable fraction]
	Stearic acid	57-11-4	8-hour TWA: 10 mg/m ³ [Stearates (except stearates of toxic metals), Inhalable fraction]
	Bounded Carbon Black	1333-86-4	Legislative Decree n.81: TWA 3.0 mg/m ³ (8 hr)
	Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	8-hour TWA: 5 mg/m ³ (Mineral oil, excluding metal working fluids, pure, highly and severely refined; Inhalable fraction)
	White Mineral Oil	8042-47-5	8-hour TWA: 5 mg/m ³ (Mineral oil, excluding metal working fluids, pure, highly and severely refined; Inhalable fraction)
	Thiram (ISO); tetramethylthiuram disulphide	137-26-8	8-hour TWA: 0.05 mg/m ³
	Heptane	142-82-5	8-hour TWA: 500 ppm (2085 mg/m ³)
	Magnesium oxide	1309-48-4	8-hour TWA: 10 mg/m ³ (inhalable fraction)
	Zinc oxide	1314-13-2	8-hour TWA: 2 mg/m ³ (Respirable fraction)
	Polyethylene	9002-88-4	8-hour TWA: 10 mg/m ³ (Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles)
	Polyethylene	9002-88-4	8-hour TWA: 3 mg/m ³ (Particles (insoluble or poorly soluble) not otherwise specified, respirable particles)
	Zinc oxide	1314-13-2	15-minute STEL: 10 mg/m ³ (Respirable fraction)
Romania	White Mineral Oil	8042-47-5	8-hour TWA: 5 mg/m ³ (Mineral oils)

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 09.12.2017

Page 11 of 26

Revision date: 04.10.2019

Butyl Liner Sealer

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	White Mineral Oil	8042-47-5	15-minute STEL: 10 mg/m ³ (Mineral oils)
	Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	8-Hour TWA: 5 mg/m ³ (Mineral oils)
	Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	15-minute STEL: 10 mg/m ³ (Mineral oils)
	Thiram (ISO); tetramethylthiuram disulphide	137-26-8	8-hour TWA: 2 mg/m ³
	Thiram (ISO); tetramethylthiuram disulphide	137-26-8	15-minute STEL: 5 mg/m ³
	Heptane	142-82-5	8-hour TWA: 2085 mg/m ³ (500 ppm)
	Zinc oxide	1314-13-2	8-hour TWA: 5 mg/m ³ (Fumes)
	Magnesium oxide	1309-48-4	8-hour TWA: 5 mg/m ³ (fumes)
	Magnesium oxide	1309-48-4	15-minute STEL: 15 mg/m ³ (fumes)
	Zinc oxide	1314-13-2	15-minute STEL: 10 mg/m ³ (Fumes)
Portugal	Stearic acid	57-11-4	8-hour Exposure Limit: 10 mg/m ³ (as stearates)
	Bounded Carbon Black	1333-86-4	VLE: 3.5 mg/m ³ (8 hr)
	Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	8-hour exposure limit: 5 mg/m ³
	White Mineral Oil	8042-47-5	NP 1796-2007 8-hour exposure limit: 5 mg/m ³
	Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	Short-term exposure limit: 10 mg/m ³
	White Mineral Oil	8042-47-5	NP 1796-2007 Short-term exposure limit: 10 mg/m ³
	Thiram (ISO); tetramethylthiuram disulphide	137-26-8	8-hour exposure limit: 1 mg/m ³
	Heptane	142-82-5	Decree-Law No. 24/2012 8-hour TWA: 500 ppm (2085 mg/m ³)
	Heptane	142-82-5	NP 1796-2007 8-hour exposure limit: 400 ppm
	Magnesium oxide	1309-48-4	8-hour exposure limit: 10 mg/m ³
	Heptane	142-82-5	NP 1796-2007 Short-term exposure limit: 500 ppm
	Polyethylene	9002-88-4	8-hour TWA: 10 mg/m ³ (Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles)
	Zinc oxide	1314-13-2	8-hour exposure limit: 2 mg/m ³
	Polyethylene	9002-88-4	8-hour TWA: 3 mg/m ³ (Particles (insoluble or poorly soluble) not otherwise specified, respirable particles)
	Zinc oxide	1314-13-2	Short-term exposure limit: 10 mg/m ³
Croatia	Bounded Carbon Black	1333-86-4	Dangerous Substances Exposure Limit Values in the Workplace: 3.5 mg/m ³ (8hr); 7.0 mg/m ³ (15 min)

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 09.12.2017

Page 12 of 26

Revision date: 04.10.2019

Butyl Liner Sealer

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Magnesium oxide	1309-48-4	Maximum (8 hr) allowable concentration: 10 mg/m ³ (total dust)
	Magnesium oxide	1309-48-4	Maximum (8 hr) allowable concentration: 4 mg/m ³ (respirable dust)
	Heptane	142-82-5	Maximum (8 hr) allowable concentration: 500 ppm (2085 mg/m ³)
	Zinc oxide	1314-13-2	Maximum (8 hr) allowable concentration: 5 mg/m ³
	Zinc oxide	1314-13-2	Short-term (15 min) allowable concentration: 10 mg/m ³
Spain	Stearic acid	57-11-4	8-hour daily exposure limit (VLA_ED): 10 mg/m ³ [Stearates (except stearates of toxic metals)]
	Bounded Carbon Black	1333-86-4	VLA: VLA_ED 3.5 mg/m ³ (8 hr)
	Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	8-hour daily exposure limit (VLA_ED): 5 mg/m ³
	White Mineral Oil	8042-47-5	8-hour daily exposure limit (VLA_ED): 5 mg/m ³
	White Mineral Oil	8042-47-5	15-minute STEL (VLA-EC): 10 mg/m ³
	Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	15-minute STEL (VLA-EC): 10 mg/m ³
	Thiram (ISO); tetramethylthiuram disulphide	137-26-8	8-hour daily exposure limit (VLA_ED): 1 mg/m ³
	Magnesium oxide	1309-48-4	8-hour daily exposure limit (VLA_ED): 10 mg/m ³
	Heptane	142-82-5	8-hour daily exposure limit (VLA_ED): 500 ppm (2085 mg/m ³)
	Polyethylene	9002-88-4	8-hour TWA: 10 mg/m ³ (Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles)
	Zinc oxide	1314-13-2	8-hour daily exposure limit (VLA_ED): 2 mg/m ³
	Polyethylene	9002-88-4	8-hour TWA: 3 mg/m ³ (Particles (insoluble or poorly soluble) not otherwise specified, respirable particles)
	Zinc oxide	1314-13-2	15-minute STEL (VLA-EC): 10 mg/m ³
Estonia	Thiram (ISO); tetramethylthiuram disulphide	137-26-8	8-hour TWA: 1 mg/m ³
	Thiram (ISO); tetramethylthiuram disulphide	137-26-8	STEL: 2 mg/m ³
	Polyethylene	9002-88-4	8-hour TWA: 10 mg/m ³ (Total Dust)
	Polyethylene	9002-88-4	8-hour TWA: 3 mg/m ³ (Dust - plastic)
	Polyethylene	9002-88-4	8-hour TWA: 5 mg/m ³ (Dust - fine dust)

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 09.12.2017

Page 13 of 26

Revision date: 04.10.2019

Butyl Liner Sealer

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Magnesium oxide	1309-48-4	8-hour TWA: 10 mg/m ³ (total dust)
	Polyethylene	9002-88-4	8-hour TWA: 1 mg/m ³ (Dust - textile)
	Heptane	142-82-5	8-hour TWA: 500 ppm (2085 mg/m ³)
	Polyethylene	9002-88-4	8-hour TWA: 5 mg/m ³ (Total dust - Organic)
	Magnesium oxide	1309-48-4	8-hour TWA: 5 mg/m ³ (fine dust)
	Magnesium oxide	1309-48-4	8-hour TWA: 3 mg/m ³ (plastic)
	Magnesium oxide	1309-48-4	8-hour TWA: 1 mg/m ³ (textile)
	Magnesium oxide	1309-48-4	8-hour TWA: 5 mg/m ³ (organic dust, total dust)
	Zinc oxide	1314-13-2	8-hour TWA: 5 mg/m ³
Cyprus	Bounded Carbon Black	1333-86-4	Control of factory atmosphere and dangerous substances in factories regulation: TWA 3.5 mg/m ³ (8 hr)
	Magnesium oxide	1309-48-4	8-hour TWA: 5 mg/m ³
	Magnesium oxide	1309-48-4	Ceiling limit (NPK-P): 10 mg/m ³
	Zinc oxide	1314-13-2	8-hour TWA: 5.0 mg/m ³ (Fumes)
Sweden	Stearic acid	57-11-4	Level Limit Value (NGV): 5 mg/m ³ (as stearates, total dust)
	Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	Level Limit Value (NGV): 1 mg/m ³ (Oil mist including oil fume)
	White Mineral Oil	8042-47-5	Level Limit Value (NGV): 1 mg/m ³ (Oil mist including oil fume)
	Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	Short Term Limit (KTV): 3 mg/m ³ (Oil mist including oil fume)
	White Mineral Oil	8042-47-5	Short Term Limit (KTV): 3 mg/m ³ (Oil mist including oil fume)
	Thiram (ISO); tetramethylthiuram disulphide	137-26-8	Level Limit Value (NGV): 1 mg/m ³
	Thiram (ISO); tetramethylthiuram disulphide	137-26-8	Short Term Limit (KTV): 2 mg/m ³
	Magnesium oxide	1309-48-4	Level Limit Value (NGV): 10 mg/m ³ (inhalable dust)
	Heptane	142-82-5	Level Limit Value (NGV): 200 ppm (800 mg/m ³)
	Magnesium oxide	1309-48-4	Level Limit Value (NGV): 5 mg/m ³ (respirable dust)
	Heptane	142-82-5	Short Term Limit (KTV): 300 ppm (1200 mg/m ³)
	Polyethylene	9002-88-4	Level limit value (NGV): 10 mg/m ³ (dust, inorganic, inhalable dust)
	Zinc oxide	1314-13-2	Level Limit Value (NGV): 5 mg/m ³ (Total dust)
	Polyethylene	9002-88-4	Level limit value (NGV): 10 mg/m ³ (dust, inorganic, respirable dust)

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 09.12.2017

Page 14 of 26

Revision date: 04.10.2019

Butyl Liner Sealer

Country (Legal Basis)	Substance	Identifier	Permissible concentration	
Slovakia	White Mineral Oil	8042-47-5	8-hour TWA (NPEL): 5 ppm (1 mg/m ³) [Liquid mineral oil mist, fumes]	
	Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	8-hour TWA (NPEL): 5 ppm (Liquid mineral oil mist, fumes)	
	White Mineral Oil	8042-47-5	15-minute STEL (NPEL): 15 ppm (3 mg/m ³) [Liquid mineral oil mist, fumes]	
	Bounded Carbon Black	1333-86-4	Regulation No. 355.2006 concerning protection of workers exposed to chemical agents, Annex 1: TWA (NPEL) 2.0 mg/m ³	
	Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	8-hour TWA (NPEL): 1 mg/m ³ (Liquid mineral oil mist, fumes)	
	Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	15-minute STEL (NPEL): 15 ppm (Liquid mineral oil mist, fumes)	
	Thiram (ISO); tetramethylthiuram disulphide	137-26-8	8-hour TWA (NPEL): 1.0 mg/m ³	
	Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	15-minute STEL (NPEL): 3 mg/m ³ (Liquid mineral oil mist, fumes)	
	Heptane	142-82-5	8-hour TWA (NPEL): 500 ppm (2085 mg/m ³)	
	Magnesium oxide	1309-48-4	8-hour TWA (NPEL): 4 mg/m ³ (respirable fraction)	
	Zinc oxide	1314-13-2	8-hour TWA (NPEL): 1 mg/m ³ [Fumes (Respirable fraction)]	
	Zinc oxide	1314-13-2	15-minute STEL (NPEL): 1 mg/m ³ [Fumes (Respirable fraction)]	
	Magnesium oxide	1309-48-4	8-hour TWA (NPEL): 10 mg/m ³ (inhalable fraction)	
	Zinc oxide	1314-13-2	8-hour TWA (NPEL): 0.1 mg/m ³ [Zinc and its inorganic compounds (Respirable fraction)]	
	Zinc oxide	1314-13-2	8-hour TWA (NPEL): 2 mg/m ³ [Zinc and its inorganic compounds (Inhalable fraction)]	
	Denmark	Polyethylene	9002-88-4	8-hour TWA: 2 mg/m ³ (Other siliceous materials (except asbestos), respirable fraction, Fr ≤ 5%)
		Polyethylene	9002-88-4	8-hour TWA (NPEL): 2 mg/m ³ (Other siliceous materials (except asbestos), respirable fraction, Fr > 5%)
Polyethylene		9002-88-4	8-hour TWA (NPEL): 10 mg/m ³ (Other siliceous materials (except asbestos), total concentration)	
Denmark	Bounded Carbon Black	1333-86-4	Exposure Limits for Substances & Materials: TWA 3.5 mg/m ³	
	White Mineral Oil	8042-47-5	TWA: 1 mg/m ³	
	Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	TWA: 1 mg/m ³	

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 09.12.2017

Page 15 of 26

Revision date: 04.10.2019

Butyl Liner Sealer

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Thiram (ISO); tetramethylthiuram disulphide	137-26-8	TWA: 1 mg/m ³
	Heptane	142-82-5	TWA: 200 ppm (820 mg/m ³)
	Magnesium oxide	1309-48-4	TWA: 6 mg/m ³
	Zinc oxide	1314-13-2	TWA: 4 mg/m ³
European Union	White Mineral Oil	8042-47-5	SCOEL 8-hour TWA: 5 mg/m ³ (severely refined mineral oils, inhalable)
	Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	8-Hour TWA: 5 mg/m ³ (Severely Refined Mineral Oils, inhalable)
	Heptane	142-82-5	IOEL threshold limit: 2085 mg/m ³ (500 ppm)
	Heptane	142-82-5	SCOEL 8-hour TWA: 500 ppm (2085 mg/m ³)
Finland	Bounded Carbon Black	1333-86-4	Workplace Exposure Limits: 3.5 mg/m ³ (8 hr); 7.0 mg/m ³ (15 min)
	White Mineral Oil	8042-47-5	8-hour limit: 5 mg/m ³
	Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	8-hour limit: 5 mg/m ³
	Thiram (ISO); tetramethylthiuram disulphide	137-26-8	8-hour limit: 1 mg/m ³
	Thiram (ISO); tetramethylthiuram disulphide	137-26-8	15-minute limit: 2 mg/m ³
	Heptane	142-82-5	8-hour limit: 300 ppm (1200 mg/m ³)
	Heptane	142-82-5	15-minute limit: 500 ppm (2100 mg/m ³)
	Magnesium oxide	1309-48-4	8-hour limit: 10 mg/m ³
	Zinc oxide	1314-13-2	8-hour limit: 2 mg/m ³
Slovenia	Thiram (ISO); tetramethylthiuram disulphide	137-26-8	8-hour TWA: 5 mg/m ³ (inhalable fraction)
	Thiram (ISO); tetramethylthiuram disulphide	137-26-8	STEL: 20 mg/m ³ (inhalable fraction)
	Heptane	142-82-5	8-hour TWA: 2085 mg/m ³ (500 ppm)
	Zinc oxide	1314-13-2	8-hour TWA: 5 mg/m ³ [Fumes (Respirable fraction)]
	Zinc oxide	1314-13-2	STEL: 20 mg/m ³ [Fumes (Respirable fraction)]
France	Bounded Carbon Black	1333-86-4	Threshold Limit Values (VLEP): Time weighted average (VME) 3.5 mg/m ³
	Thiram (ISO); tetramethylthiuram disulphide	137-26-8	Time weighted average (VME): 5 mg/m ³
	Heptane	142-82-5	Time weighted average (VME): 400 ppm (1668 mg/m ³)
	Magnesium oxide	1309-48-4	Time weighted average (VME): 10 mg/m ³ (fumes)
	Heptane	142-82-5	Short term exposure limit: 500 ppm (2085 mg/m ³)

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 09.12.2017

Page 16 of 26

Revision date: 04.10.2019

Butyl Liner Sealer

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Polyethylene	9002-88-4	Time weighted average: 10 mg/m ³ (Inhalable fraction)
	Zinc oxide	1314-13-2	Time weighted average (VME): 5 mg/m ³ (Fumes)
	Polyethylene	9002-88-4	Time weighted average: 5 mg/m ³ (Respirable fraction)
	Zinc oxide	1314-13-2	Time weighted average (VME): 10 mg/m ³ (Dusts)
Latvia	Heptane	142-82-5	8-hour TWA: 350 mg/m ³ (85 ppm)
	Heptane	142-82-5	15-minute STEL: 2085 mg/m ³ (500 ppm)
	Polyethylene	9002-88-4	8-hour TWA: 5 mg/m ³ (Polymer dust)
	Polyethylene	9002-88-4	8-hour TWA: 2 mg/m ³ (Silicates and aluminosilicates: abrasive dusts)
	Polyethylene	9002-88-4	8-hour TWA: 2 mg/m ³ (Silicates and aluminosilicates: bauxite ore)
	Polyethylene	9002-88-4	8-hour TWA: 4 mg/m ³ (Silicates and aluminosilicates: mica, phlogopite, muscovite, talc, talc-like dust)
	Polyethylene	9002-88-4	8-hour TWA: 2 mg/m ³ (Silicates and aluminosilicates: synthetic mineral fiber with silicates and aluminosilicates of glasslike structure (fiberglass, glass-wool, cinder, and silicate cotton, etc.))
	Polyethylene	9002-88-4	8-hour TWA: 6 mg/m ³ (Silicates and aluminosilicates: cement, apatite, clay)
	Zinc oxide	1314-13-2	8-hour TWA: 0.5 mg/m ³
	Polyethylene	9002-88-4	8-hour TWA: 4 mg/m ³ (Silicates and aluminosilicates: volcanic origin glasslike silicates (tuff, pumice, perlite))
Polyethylene	9002-88-4	8-hour TWA: 2 mg/m ³ (Silicates and aluminosilicates: zeolites (natural and synthetic))	
Greece	Bounded Carbon Black	1333-86-4	Decree 307/1986: TWA 3.5mg/m ³ (8 hr); STEL 7.0 mg/m ³ (15 min)
	Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	8-hour TWA: 5 mg/m ³ (Paraffin oil, mist)
	White Mineral Oil	8042-47-5	8-hour TWA: 5 mg/m ³ [Paraffin oil (Mist)]
	Thiram (ISO); tetramethylthiuram disulphide	137-26-8	8-hour TWA: 5 mg/m ³
	Thiram (ISO); tetramethylthiuram disulphide	137-26-8	15-minute STEL: 10 mg/m ³
	Magnesium oxide	1309-48-4	8-hour TWA: 10 mg/m ³ (inhalable)
	Heptane	142-82-5	8-hour TWA: 500 ppm (2000 mg/m ³)

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 09.12.2017

Page 17 of 26

Revision date: 04.10.2019

Butyl Liner Sealer

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Magnesium oxide	1309-48-4	8-hour TWA: 5 mg/m ³ (respirable)
	Heptane	142-82-5	15-minute STEL: 500 ppm (2000 mg/m ³)
	Zinc oxide	1314-13-2	8-hour TWA: 5 mg/m ³ (Fumes)
	Zinc oxide	1314-13-2	15-minute STEL: 10 mg/m ³ (Fumes)
Austria	Thiram (ISO); tetramethylthiuram disulphide	137-26-8	TWA: 5 mg/m ³
	Thiram (ISO); tetramethylthiuram disulphide	137-26-8	STEL: 25 mg/m ³
	Heptane	142-82-5	TWA: 2000 mg/m ³ (500 ppm)
	Heptane	142-82-5	STEL: 8000 mg/m ³ (2000 ppm)
Germany	White Mineral Oil	8042-47-5	AGW limit value: 5 mg/m ³
	White Mineral Oil	8042-47-5	AGW Short term (15 min) exposure limit: 20 mg/m ³
	Thiram (ISO); tetramethylthiuram disulphide	137-26-8	AGW limit value: 1 mg/m ³ (inhalable fraction)
	Thiram (ISO); tetramethylthiuram disulphide	137-26-8	AGW Short term (15 min) exposure limit: 2 mg/m ³ (inhalable fraction)
	Heptane	142-82-5	AGW limit value: 500 ppm (2100 mg/m ³)
	Magnesium oxide	1309-48-4	AGW Limit value: 1.25 mg/m ³ (respirable fraction)
	Heptane	142-82-5	AGW Short term (15 min) exposure limit: 500 ppm (2100 mg/m ³)
	Magnesium oxide	1309-48-4	AGW limit value: 10 mg/m ³ (inhalable fraction)
	Polyethylene	9002-88-4	8-hour TWA: 4 mg/m ³ (General threshold limit value. Inhalable fraction)
Malta	Heptane	142-82-5	TWA: 500 ppm (2085 mg/m ³)
United Kingdom	Bounded Carbon Black	1333-86-4	WEL: TWA 3.5 mg/m ³ ; STEL 7.0 mg/m ³
	Magnesium oxide	1309-48-4	TWA: 10 mg/m ³ as Mg (inhalable dust)
	Magnesium oxide	1309-48-4	TWA: 4 mg/m ³ as Mg (fume and respirable dust)
	Heptane	142-82-5	TWA: 500 ppm (2085 mg/m ³)
	Polyethylene	9002-88-4	TWA: 4 mg/m ³ (Dust: respirable dust)
	Polyethylene	9002-88-4	TWA: 10 mg/m ³ (Dust: inhalable dust)
Netherlands	Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	8-Hour TWA: 5 mg/m ³ (Mineral oils, mist)
	White Mineral Oil	8042-47-5	Binding 8-hour TWA: 5 mg/m ³ [Oil mist (Mineral oil)]
	Heptane	142-82-5	Binding 8-hour TWA: 1200 mg/m ³

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 09.12.2017

Page 18 of 26

Revision date: 04.10.2019

Butyl Liner Sealer

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Heptane	142-82-5	Binding STEL (15 min): 1600 mg/m ³
Luxembourg	Heptane	142-82-5	TWA: 500 ppm (2085 mg/m ³)

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Derived No Effect Level (DNEL):

Not determined or not applicable.

Predicted No Effect Concentration (PNEC):

Not determined or not applicable.

Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. Biological monitoring may also be appropriate for some substances.

8.2 Exposure controls

Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above.

Use explosion-proof ventilation equipment.

Personal protection equipment

Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

Skin and body protection:

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

For continuous contact we recommend nitrile gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified.

Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.

Always seek advice from glove suppliers.

Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Use a European Standard EN149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. Comply with the European Standard EN149.

General hygienic measures:

Avoid contact with skin, eyes and clothing.

Wash hands before breaks and at the end of work.

Wash contaminated clothing before reuse.

Environmental exposure controls:

Select controls based on a risk assessment of local conditions.

See section 6 for information on accidental release measures.

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 09.12.2017

Page 19 of 26

Revision date: 04.10.2019

Butyl Liner Sealer

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	Black viscous liquid
Odor	Strong solvent
Odor threshold	Not determined or not available.
pH	Not determined or not available.
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	190°F (88°C)
Flash point (closed cup)	15°F (-9°C)
Evaporation rate	> 1 (n-BuAC = 1)
Flammability (solid, gas)	Flammable
Upper flammability/explosive limit	6.7% (V)
Lower flammability/explosive limit	1.2% (V)
Vapor pressure	119 mmHg at 20°C (68°F)
Vapor density	Not determined or not available.
Density	Not determined or not available.
Relative density	0.77 g/cm ³ (6.59 lbs./gal) at 20°C
Solubilities	Not determined or not available.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	7000 cps
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

9.2 Other information

VOC	567 g/L
-----	---------

SECTION 10: Stability and reactivity

10.1 Reactivity:

Does not react under normal conditions of use and storage.

10.2 Chemical stability:

Stable under normal conditions of use and storage.

10.3 Possibility of hazardous reactions:

None under normal conditions of use and storage.

10.4 Conditions to avoid:

Prevent exposure to heat, sparks, flame and other sources of ignition.

10.5 Incompatible materials:

None known.

10.6 Hazardous decomposition products:

None known.

SECTION 11: Toxicological information

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 09.12.2017

Page 20 of 26

Revision date: 04.10.2019

Butyl Liner Sealer

11.1 Information on toxicological effects

Acute toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Route	Result
Heptane	inhalation	LC50 Rat: > 29.29 mg/L (4 hr)
	oral	LD50 Rat: > 5000 mg/kg
Thiram (ISO); tetramethylthiuram disulphide	oral	LD50 - Bird (Wild) - 300 mg/kg
	inhalation	LC50 - Rat - 3.464 mg/L air (analytical) - 4 h

Skin corrosion/irritation

Assessment:

Causes skin irritation

Product data:

No data available.

Substance data:

Name	Result
Heptane, branched, cyclic and linear	Causes skin irritation.
Heptane	Causes skin irritation.

Serious eye damage/irritation

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Respiratory or skin sensitization

Assessment:

May cause an allergic skin reaction

Product data:

No data available.

Substance data:

Name	Result
Di(benzothiazol-2-yl) disulphide	May cause sensitization by skin contact.
Thiram (ISO); tetramethylthiuram disulphide	May cause an allergic skin reaction.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Species	Result
Distillates (petroleum), hydrotreated heavy paraffinic	Not applicable.	The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346.

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 09.12.2017

Page 21 of 26

Revision date: 04.10.2019

Butyl Liner Sealer

Name	Species	Result
Bounded Carbon Black	Not applicable.	The carcinogenic classification only applies to airborne, unbound particles of respirable size.
Magnesium oxide	Not applicable	American Conference of Governmental Industrial Hygienists - A4: Not classifiable as a human carcinogen

International Agency for Research on Cancer (IARC):

Name	Classification
Bounded Carbon Black	Group 2B - Possibly carcinogenic to humans
Polyethylene	Group 3 - Not classifiable as to its carcinogenicity to humans

National Toxicology Program (NTP): None of the ingredients are listed.

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

Reproductive Toxicity

Assessment:

Suspected of damaging fertility or the unborn child

Product data:

No data available.

Substance data:

Name	Result
2,2'-Methylenebis(4-methyl-6-tertiarybutyl phenol)	Suspected of damaging fertility or the unborn child.

Specific target organ toxicity (single exposure)

Assessment:

May cause drowsiness or dizziness

Product data:

No data available.

Substance data:

Name	Result
Heptane, branched, cyclic and linear	May cause drowsiness or dizziness.
Heptane	May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
Thiram (ISO); tetramethylthiuram disulphide	May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 09.12.2017

Page 22 of 26

Revision date: 04.10.2019

Butyl Liner Sealer

Substance data:

Name	Result
Heptane, branched, cyclic and linear	May be fatal if swallowed and enters airways.
Heptane	May be fatal if swallowed and enters airways.

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

Other information:

No data available.

SECTION 12: Ecological information

12.1 Toxicity

Acute (short-term) toxicity

Assessment:

Toxic to aquatic life

Product data: No data available.

Substance data:

Name	Result
2,2'-Methylenebis(4-methyl-6-tertiarybutyl phenol)	EC50 (48 h): 4.8 mg/L
	NOEC (21 days): 340 µg/L
	EC50 (72 h): 5 mg/L
Thiram (ISO); tetramethylthiuram disulphide	LC50 - Oncorhynchus mykiss (Rainbow trout) - 0.046 mg/L - 96 h
	EC50 - Daphnia magna (Water flea) - 0.38 mg/L - 48 h
	NOEC - Pimephales promelas - 0.0046 mg/L - 33 d
Heptane	NOEC - Daphnia magna - 0.02 mg/L - 21 d
	LC50 - Carassius auratus (goldfish) - 4 mg/l - 24.0 h
Zinc oxide	EC50 - Daphnia magna - 82.5 mg/L - 96 h
	Oncorhynchus mykiss (rainbow trout) - 1.1 mg/l - 96.0 h
	Daphnia magna (Water flea) - 0.098 mg/l - 48 h

Chronic (long-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Result
2,2'-Methylenebis(4-methyl-6-tertiarybutyl phenol)	NOEC (21 days): 340 µg/L
Thiram (ISO); tetramethylthiuram disulphide	NOEC - Pimephales promelas - 0.0046 mg/L - 33 d
	NOEC - Daphnia magna - 0.02 mg/L - 21 d

12.2 Persistence and degradability

Product data: No data available.

Substance data:

Name	Result
Heptane	Readily biodegradable in water.

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 09.12.2017

Page 23 of 26

Revision date: 04.10.2019

Butyl Liner Sealer

12.3 Bioaccumulative potential

Product data: No data available.

Substance data:

Name	Result
Heptane	Calculated BCF: 552 (Not expected to bioaccumulate).

12.4 Mobility in soil

Product data: No data available.

Substance data:

Name	Result
Heptane	Moderately Mobile (log Koc: 2.38)

12.5 Results of PBT and vPvB assessment

PBT assessment:

Heptane	This substance is not PBT.
---------	----------------------------

vPvB assessment:

Heptane	This substance is not vPvB.
---------	-----------------------------

12.6 Other adverse effects: No data available.

SECTION 13: Disposal considerations



13.1 Waste treatment methods

Relevant information:



It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

SECTION 14: Transport information

International Carriage of Dangerous Goods by Road/Rail (ADR/RID)

UN number	UN1133
UN proper shipping name	Adhesives
UN transport hazard class(es)	3  
Packing group	II
Environmental hazards	Marine Pollutant (Heptane and Heptane, Branched, cyclic and linear)
Special precautions for user	None

International Carriage of Dangerous Goods by Inland Waterways (ADN)

UN number	UN1133
UN proper shipping name	Adhesives
UN transport hazard class(es)	3  
Packing group	II
Environmental hazards	Marine Pollutant (Heptane and Heptane, Branched, cyclic and linear)
Special precautions for user	None

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)



Initial preparation date: 09.12.2017

Page 24 of 26



Revision date: 04.10.2019

Butyl Liner Sealer

International Maritime Dangerous Goods (IMDG)

UN number	UN1133
UN proper shipping name	Adhesives
UN transport hazard class(es)	3  
Packing group	II
Environmental hazards	Marine Pollutant (Heptane and Heptane, Branched, cyclic and linear)
Special precautions for user	None

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	UN1133
UN proper shipping name	Adhesives
UN transport hazard class(es)	3  
Packing group	II
Environmental hazards	Marine Pollutant (Heptane and Heptane, Branched, cyclic and linear)
Special precautions for user	None

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Bulk Name	None
Ship type	None
Pollution category	None

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

European regulations

Inventory listing (EINECS):

64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic	Listed
1333-86-4	Bounded Carbon Black	Listed
1309-48-4	Magnesium oxide	Listed
57-11-4	Stearic acid	Listed
119-47-1	2,2'-Methylenebis(4-methyl-6-tertiarybutyl phenol)	Listed
9002-88-4	Polyethylene	Not Listed
1314-13-2	Zinc oxide	Listed
120-78-5	Di(benzothiazol-2-yl) disulphide	Listed
137-26-8	Thiram (ISO); tetramethylthiuram disulphide	Listed
8042-47-5	White Mineral Oil	Listed
426260-76-6	Heptane, branched, cyclic and linear	Not Listed

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 09.12.2017

Page 25 of 26

Revision date: 04.10.2019

Butyl Liner Sealer

142-82-5	Heptane	Listed
----------	---------	--------

REACH SVHC candidate list: None of the ingredients are listed.

REACH SVHC Authorizations: None of the ingredients are listed.

REACH Restriction: None of the ingredients are listed.

Water hazard class (WGK) (Product): Not determined.

Water hazard class (WGK) (Substance):

Ingredient Name	CAS	Class
Bounded Carbon Black	1333-86-4	Non-hazardous to water.
Stearic acid	57-11-4	Non-hazardous to water.
Zinc oxide	1314-13-2	2
White Mineral Oil	8042-47-5	1
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	1
Magnesium oxide	1309-48-4	1
2,2'-Methylenebis(4-methyl-6-tertiarybutyl phenol)	119-47-1	1
Polyethylene	9002-88-4	Not applicable.
Thiram (ISO); tetramethylthiuram disulphide	137-26-8	3
Di(benzothiazol-2-yl) disulphide	120-78-5	2
Heptane, branched, cyclic and linear	426260-76-6	Not applicable.
Heptane	142-82-5	2

Other regulations

Germany TA Luft: None of the ingredients are listed.

Germany MAK: Zinc oxide: 8-hour TWA: 0.1 mg/m³ [Zinc and its inorganic compounds (respirable fraction)], Zinc oxide: 8-hour TWA: 2 mg/m³ [Zinc and its inorganic compounds (inhalable fraction)], Magnesium oxide: 8-hour TWA: 1.5 mg/m³ (respirable fraction), Magnesium oxide: 8-hour TWA: 4 mg/m³ (inhalable fraction), Thiram (ISO); tetramethylthiuram disulphide: 8-hour TWA: 1 mg/m³ (inhalable fraction), White Mineral Oil: 8-hour TWA: 5 mg/m³ (respirable fraction), Heptane: 8-hour TWA: 500 ppm (2100 mg/m³)

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other information

Indication of changes:

April 10, 2019: Composition change, consequently changing the occupational exposure limits and a change in classification

Abbreviations and Acronyms: None

Classification procedure:

Classification according to Regulation (EC) No. 1272/2008 (CLP)	Method Used
Flammable liquids, category 2	Calculation method
Skin irritation, category 2	Calculation method

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 09.12.2017

Page 26 of 26

Revision date: 04.10.2019

Butyl Liner Sealer

Classification according to Regulation (EC) No. 1272/2008 (CLP)	Method Used
Skin sensitization, category 1	Calculation method
Specific target organ toxicity - single exposure, category 3, central nervous system	Calculation method
Reproductive toxicity, category 2	Calculation method
Chronic aquatic hazard, category 2	Calculation method

Summary of classification in section 3:

Asp. Tox. 1; H304	Aspiration hazard, category 1
Aquatic Chronic 2; H411	Chronic aquatic hazard, category 2
Flam. Liq. 2; H225	Flammable liquids, category 2
Stot SE 3; H336	Specific target organ toxicity - single exposure, category 3, central nervous system
Skin Irrit. 2 ; H315	Skin irritation, category 2
Aquatic Acute 1; H400	Acute aquatic hazard, category 1
Aquatic Chronic 1; H410	Chronic aquatic hazard, category 1
Skin Sens. 1; H317	Skin sensitization, category 1
Acute Tox. 4; H302	Acute toxicity (oral), category 4
Acute Tox. 4; H332	Acute toxicity (inhalation), category 4
Eye Irrit. 2; H319	Eye irritation, category 2A
Stot RE 2; H373	Specific target organ toxicity - repeated exposure, category 2
Repr. 2; H361	Reproductive toxicity, category 2
Aquatic Chronic 4; H413	Chronic aquatic hazard, category 4

Summary of hazard statements in section 3:

H304	May be fatal if swallowed and enters airways
H411	Toxic to aquatic life with long lasting effects
H225	Highly flammable liquid and vapour
H336	May cause drowsiness or dizziness
H315	Causes skin irritation
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H317	May cause an allergic skin reaction
H302	Harmful if swallowed
H332	Harmful if inhaled
H319	Causes serious eye irritation
H373	May cause damage to organs through prolonged or repeated exposure
H361	Suspected of damaging fertility or the unborn child
H413	May cause long lasting harmful effects to aquatic life

Disclaimer:

This product has been classified in accordance with EC No. 1272/2008 (CLP) and EC No. 1907/2006 (REACH). The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

Initial preparation date: 09.12.2017

Revision date: 04.10.2019

End of Safety Data Sheet