



### QUICK RELEASE ADAPTORS - ERP 07


- ID Passage **7,2 - 7,4 mm**
- Pressure **P.N. 16 bar**
- Accuracy **Precise dimensions**
- Hardness **Abrasion-resistant**
- Construction **Treated steel**



	A	B	DESCRIPTION	REFERENCE
<b>Female threaded adaptor</b>	40	15	G 1/4	<b>ERP 076101</b>
	41	21	G 3/8	<b>ERP 076102</b>
	44	27	G 1/2	<b>ERP 076103</b>
<b>Tapered thread male adaptor</b>			<b>Teflon-coated threading</b>	
	35.5	13	R 1/4 - Teflon-coated	<b>ERP 076151</b>
	41	17	R 3/8 - Teflon-coated	<b>ERP 076152</b>
	52	24	R 1/2 - Teflon coated	<b>ERP 076153</b>
<b>Hose tail adaptor</b>	44.5		Ø 6 mm	<b>ERP 076806</b>
	46		Ø 8 mm	<b>ERP 076808</b>
	46		Ø 10 mm	<b>ERP 076810</b>
	51.5		Ø 13 mm	<b>ERP 076813</b>



Female threaded adaptor



Tapered thread male adaptor



Hose tail adaptor